



PRODUCT DATA SHEET

SYNPLUS ACEA C2 PLUS 0W/30

PRODUCT DESCRIPTION

SYNPLUS ACEA C2 PLUS 0W/30 is a full synthetic, low to mid SAPS, super high performance engine oil specifically blended to meet the ACEA C2 and Ford WSS-M2C950-A performance levels. It combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection whilst promoting fuel efficiency in modern low friction engines in high performance car, light van diesel and gasoline vehicles.

SYNPLUS ACEA C2 PLUS 0W/30 is a stable, stay-in-grade catalyst compatible oil intended for use at extended drain intervals in car and light van diesel engines with catalytic converter exhaust systems. These engines will be designed to be capable of using this low friction, low viscosity oil with a high temperature/high shear rate (HTHS) viscosity of 2.9 mPa-s minimum.

SYNPLUS ACEA C2 PLUS 0W/30 meets the 2016 edition of the ACEA C2 specification including increased sludge handling performance to further increase the long drain capabilities of this oil, and extension to the life of catalytic, diesel particulate or three-way exhaust systems.

SYNPLUS ACEA C2 PLUS 0W/30 meets today's environmentally conscious market demands of reduced emissions and increased fuel efficiency.

BENEFITS

- Longer drain intervals
- Better fuel economy
- Longer life for catalytic exhaust systems
- Preserved performance of DPF and TWC filter systems

SPECIFICATIONS:

SYNPLUS ACEA C2 PLUS 0W/30 meets or exceeds the following demanding performance level:

| | |
|--------------------|---------------|
| ACEA: | C2 |
| Ford: | WSS-M2C950-A |
| Jaguar-Land Rover: | STJLR.03.5007 |

Always consult your vehicle owner's manual for the manufacturer's lubricant recommendations.

TYPICAL PROPERTIES

| Property | Typical Results |
|------------------------|-----------------|
| Appearance | Amber |
| Density (kg/Lt) @15°C | 0.852 |
| Viscosity (cSt) @100°C | 9.6 |
| @40°C | 48.4 |
| CCS @ -35°C (cP) | 6020 |
| Viscosity Index | 188 |
| HTHS (cP) | 3.0 |
| TBN (mg KOH/g) | 7.7 |
| Sulphated Ash (% wt) | 0.8 |
| Phosphorus (% wt) | 0.07 |
| Flash Point (°C) | 215 |



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Available in: Bulk, 1000 Litres, 200 Litres, 20 Litres, 10 Litres and 5 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI1-2140

Effective: March 2022

MR223003/1



AUSTRALIAN FAMILY OWNED SINCE 1989

