



PRODUCT DATA SHEET

TOLUENE SOLVENT

PRODUCT DESCRIPTION

Hi-Tec Toluene Solvent is a narrow boiling range, medium evaporating solvent for uses where high solvency is required.

QUALITY

Hi-Tec Toluene Solvent does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

STORAGE AND HANDLING

Provided proper storage and handling precautions are taken we would expect **Hi-Tec Toluene Solvent** to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Materials Safety Data Sheet.

TYPICAL PROPERTIES

Property	Unit	Method	Value
Density @ 15°C	kg/l	ASTM D4052	0.869
Colour	Saybolt	ASTM D156	+30
Distillation, IBP	°C	ASTM D1078	110
Distillation, DP	°C	ASTM D1078	111
Paraffins	% m/m	GC	<1
Naphthenes	% m/m	GC	<1
Aromatics	% m/m	GC	99
Benzene	% m/m	GC	0.03
Flash Point	°C	IP 170	4
Electrical Conductivity @ 23°C	pS/m	ASTM D2624	400

Available in:

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: IN8-3465

Effective: September 2013

Expires: September 2015

JN319091/1

