



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

X55

PRODUCT DESCRIPTION

X55 Solvent is a wide boiling range, rapidly evaporating, residue free solvent used for processing, cleaning and degreasing in many industries including printing, paints, adhesives and rubber manufacture. It does not mix with water and does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds

TYPICAL PROPERTIES

Property	Results
Appearance	Clear, colourless liquid.
Density @ 15°C, kg/L	0.685 – 0.720
Flash Point, °C	< -20
Boiling Point, °C	66 – 115
Auto-ignition Temperature, °C	350

TRANSPORT AND HANDLING

UN No.	1268
Dangerous Goods Class	3, Flammable Liquids
Hazchem Code	3YE
Packaging Group	II

Refer to the Safety Data Sheet for safety instructions prior to handling.

Available in: 200 Litres and 20 Litres

“Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au”

Item Code: HI8-3570

Effective: March 2020

MR023060/1



AUSTRALIAN FAMILY OWNED SINCE 1989

