



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

SAFETY DATA SHEET

Page 1 of 10
Issue Date: 7 April 2022
Brake & Parts Cleaner
Version: 6

Product name: Brake & Parts Cleaner

1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY: Hi-Tec Oil Traders Pty Ltd. (ABN 28 053 837 362)

ADDRESS: PO Box 322 Castle Hill NSW 1765
5 Tarlington Place, Smithfield NSW 2164

TELEPHONE NUMBER: 1300 796 009

FAX NUMBER: (02) 9604 1611

EMERGENCY TELEPHONE NUMBER: 1300 796 009

PRODUCT NAME: Brake & Parts Cleaner

OTHER NAMES: None

MANUFACTURER'S PRODUCT CODE: HI8-8210

USE: Clear, colourless liquid for cleaning brake drums and disks

ADDITIONAL INFORMATION: Refer to Product Information Sheet for additional information.

OTHER INFORMATION: Visit our website: www.hi-tecoils.com.au
Email: hitecoils@hi-tecoils.com.au

2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE: HAZARDOUS SUBSTANCE
DANGEROUS GOODS
Hazard classification according to Australian WHS Regulations.

DANGEROUS GOODS CLASS: 2.1: Flammable gases



SIGNAL WORD: DANGER



AUSTRALIAN FAMILY OWNED SINCE 1989





SAFETY DATA SHEET

Page 2 of 10
Issue Date: 7 April 2022
Brake & Parts Cleaner
Version: 6

2. HAZARDS IDENTIFICATION (CONT)

GHS HAZARD CLASSIFICATION

FLAMMABLE AEROSOLS:

Category 1

SKIN IRRITATION:

Category 2

SERIOUS EYE IRRITATION:

Category 2/2A

SPECIFIC TARGET ORGAN TOXICITY

- SINGLE EXPOSURE:

Category 3

SPECIFIC TARGET ORGAN TOXICITY

- REPEATED EXPOSURE:

Category 1

HAZARD STATEMENTS:

H222: Extremely flammable aerosol

H229: Pressurised container; may burst if heated.

AUH066: Repeated exposure may cause skin dryness or cracking.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs through prolonged or repeated exposure.

PREVENTION STATEMENTS:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE STATEMENTS:

P314: Get medical advice or attention if you feel unwell.

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P372: Explosion risk in case of fire.

P381: Eliminate all ignition sources if safe to do so.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam. Water fog or fine spray is the preferred medium for large fires.

STORAGE STATEMENTS:

P403: Store in a well-ventilated place.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.



SAFETY DATA SHEET

2. HAZARDS IDENTIFICATION (CONT)

DISPOSAL STATEMENT:

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).None Allocated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient | CAS NO | CONTENT |
|--------------------------|------------|----------|
| Alkanes C ₃₋₄ | 64745-59-2 | 20 - 40% |
| Mixed Heptanes | 106-97-8 | to 100% |

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

4. FIRST AID MEASURES

GENERAL INFORMATION:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

INHALATION:

First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

SKIN CONTACT:

Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

EYE CONTACT:

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

INGESTION:

If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.



SAFETY DATA SHEET

Page 4 of 10

Issue Date: 7 April 2022

Brake & Parts Cleaner

Version: 6

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:

In case of fire, use carbon dioxide, dry chemical or foam. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

FIRE AND EXPLOSION HAZARDS:

The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

FIRE FIGHTING:

If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE:

In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC, Nitrile. Eye/face protective equipment should comprise, as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Take suitable precautions e.g. use of non-sparking equipment to avoid creating sparks or flames which may ignite the spilled material. Leaking gases may form an explosion hazard. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.



SAFETY DATA SHEET

Page 5 of 10

Issue Date: 7 April 2022

Brake & Parts Cleaner

Version: 6

7. HANDLING AND STORAGE

HANDLING:

Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

STORAGE:

This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool (below 30°C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: **AS/NZS 4501 set 2008**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**

SWA Exposure Limits

TWA (mg/m³)

STEL (mg/m³)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

VENTILATION:

This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

EYE PROTECTION:

Protective glasses or goggles must be worn when this product is being used. Failure to protect your eyes may lead to severe harm to them or to general health. Emergency eye wash facilities must also be available in an area close to where this product is being used.

SKIN PROTECTION:

Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

PROTECTIVE MATERIAL TYPES:

We suggest that protective clothing be made from the following materials: butyl rubber, Teflon, PE/EVAL, Responder.

RESPIRATOR:

Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

OTHER:

Eyebaths or eyewash stations and Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.





SAFETY DATA SHEET

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-------------------------------|--|
| FORM: | Clear liquid dispensed as aerosol spray |
| ODOUR: | Solvent odour |
| BOILING POINT: | Not available |
| FLASH POINT: | Not available |
| UPPER FLAMABILITY LIMIT: | Not available |
| LOWER FLAMABILITY LIMIT): | Not available |
| AUTOIGNITION TEMPERATURE: | No data |
| FREEZING/MELTING POINT: | No specific data. Liquid at normal temperatures. |
| VOLATILES: | No data |
| VAPOUR PRESSURE: | No data |
| VAPOUR DENSITY: | No data |
| SPECIFIC GRAVITY: | No data |
| WATER SOLUBILITY: | Miscible |
| pH: | No data |
| VOLATILITY: | No data |
| ODOUR THRESHOLD: | No data |
| EVAPORATION RATE: | No data |
| COEFF OIL/WATER DISTRIBUTION: | No data |
| PARTICLE CHARACTERISTICS: | Not applicable for liquids |

10. STABILITY AND REACTIVITY

| | |
|-------------|--|
| REACTIVITY: | This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties. |
|-------------|--|



SAFETY DATA SHEET

Page 7 of 10

Issue Date: 7 April 2022

Brake & Parts Cleaner

Version: 6

10. STABILITY AND REACTIVITY (CONT)

CONDITIONS TO AVOID:

Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

INCOMPATIBLE MATERIALS:

Oxidising agents.

FIRE DECOMPOSITION:

Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

POLYMERISATION:

This product will not undergo polymerisation reactions.

11. TOXICOLOGICAL INFORMATION

LOCAL EFFECTS

TARGET ORGANS:

There is no data to hand indicating any particular target organs. Alkanes, C3-4 is an SWA Class 2 Mutagen, likely to be mutagenic to humans.

CLASSIFICATION OF HAZARDOUS INGREDIENTS

INGREDIENT:

Hydrocarbons, C3-4

- Gases under pressure
- Flammable gas – category 1
- Acute toxicity – category 2
- Carcinogenicity – category 1A
- Germ cell mutagenicity – category 1B
- Eye irritation – category 2A
- Skin irritation – category 2
- Specific target organ toxicity (single exposure) – category 3
- Specific target organ toxicity (repeated exposure) – category 1
- Reproductive toxicity – category 1B

NOTE: Some of the above classifications relate to impurities present in some grades of these ingredients. They do not apply in situations where the impurities are not present at hazardous concentrations.

INHALATION:

Short Term Exposure: High vapour pressures may cause drowsiness and dizziness. In addition product is unlikely to cause any discomfort or irritation. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

Long Term Exposure: Vapours may cause drowsiness and dizziness.



SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION (CONT)

SKIN CONTACT:

Short Term Exposure: Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

Long Term Exposure: Repeated exposure may cause skin dryness or cracking.

EYE CONTACT:

Short Term Exposure: If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

Long Term Exposure: No data for health effects associated with long term eye exposure.

INGESTION:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is not harmful. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

CARCINOGEN STATUS:

SWA: Hydrocarbons, C₃₋₄ is classified by SWA as a Category 1b Carcinogen. See the SWA website for further details. A web address has not been provided as addresses frequently change.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

12. ECOLOGICAL INFORMATION

Insufficient data to be sure of status.

13. DISPOSAL CONSIDERATIONS

DISPOSAL:

Containers should be emptied as completely as practical before disposal. If possible, recycle product and containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Do not puncture or incinerate aerosol cans, even when empty.



SAFETY DATA SHEET

14. TRANSPORT INFORMATION

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria for land, air and sea transport.



| | |
|------------------------------|--|
| UN NO: | 1950, AEROSOLS |
| HAZCHEM CODE: | 2YE |
| SPECIAL PROVISIONS: | 63, 190, 277, 327, 344, 381 |
| LIMITED QUANTITIES: | ADG 7 specifies a Limited Quantity value of 1000mL for this class of product. |
| DANGEROUS GOODS CLASS: | 2.1: Flammable gases |
| PACKING GROUP: | Not set |
| PACKING INSTRUCTION: | P207, LP200 |
| PROPER SHIPPING NAME: | AEROSOLS |
| SEGREGATION DANGEROUS GOODS: | Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties. |

15. REGULATORY INFORMATION

| | |
|------------------------------|---|
| POISON SCHEDULE: | None allocated |
| PACKING & LABELLING: | Refer to Section 14. |
| AUSTRALIAN INVENTORY STATUS: | All components are listed on AICS, or exempt. |



SAFETY DATA SHEET

16. OTHER INFORMATION

CONTACT PERSON/POINT: General Manager 1300 796 009

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

LITERATURE REFERENCES:

- * NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets.
- * Safe Work Australia: 2016 Preparation of Safety Data Sheets for Hazardous Chemicals.
- * NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances.
- * NOHSC: 10005 List of Designated Hazardous Substances.
- * NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice.
- * NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice.
- * NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards.
- * NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note.
- * NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard.
- * NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice.
- * SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons
- * ADG: Australian Dangerous Goods Code
- * MSDS of component materials.

LAST CHANGE: Supercedes document issued: 27 August 2018.
Reason/s for revision: Minor editorial changes to comply with GHS requirements.

MR224070/1

END OF SDS