



Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

# SAFETY DATA SHEET

Page 1 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

**Product name:** Concrete Floor Powder

### 1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY: Hi-Tec Oil Traders Pty Ltd. (ABN 28 053 837 362)

ADDRESS: PO Box 322 Castle Hill NSW 1765

5 Tarlington Place, Smithfield NSW 2164

TELEPHONE NUMBER: 1300 796 009

FAX NUMBER: (02) 9604 1611

EMERGENCY TELEPHONE NUMBER: 1300 796 009

PRODUCT NAME: Concrete Floor Powder

OTHER NAMES: None

MANUFACTURER'S PRODUCT CODE: HI8-3075

USE: For cleaning concrete

ADDITIONAL INFORMATION: Refer to Product Information Sheet for additional information.

OTHER INFORMATION: Visit our website: <a href="www.hi-tecoils.com.au">www.hi-tecoils.com.au</a>
Email: hitecoils@hi-tecoils.com.au

### 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE: HAZARDOUS SUBSTANCE

NON-DANGEROUS GOODS

Hazard classification according to criteria of NOHSC and GHS

Dangerous goods classification according to the Australian Dangerous Goods Code.

POISON SCHEDULE: S5

UN / ADG NO: None allocated

**GHS LABEL ELEMENTS** 



SIGNAL WORD: WARNING









Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

# Y DATA SH

Page 2 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

### 2. HAZARDS IDENTIFICATION (CONT)

#### GHS HAZARD CLASSIFICATIONS

HAZARD STATEMENTS: H315: Causes skin irritation.

H320: Causes eye irritation.

H335: May cause respiratory irritation.

PREVENTION STATEMENTS: P102: Keep out of reach of children.

P261: Avoid breathing fumes, mists, vapours or spray. P262: Do not get in eyes, on skin, or on clothing. P264: Wash contacted areas thoroughly after handling. P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE STATEMENTS: P312: Call the POISON INFORMATION CENTER on 13 11 26 or doctor if you feel

unwell.

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice. P337+P313: If eve irritation persists: Get medical advice.

P370+P378: Not combustible. Use extinguishing media suited to burning materials.

P402+P404: Store in a dry place. Store in a closed container. STORAGE STATEMENT(S):

P403+P235: Store in a well-ventilated place. Keep cool.

**DISPOSAL STATEMENT:** P501: Dispose of contents/container in accordance with local, regional, national and

international regulations.









Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765 Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

# Y DATA SH

Page 3 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERISTICS: Alkaline powder

INGREDIENTS:-

CHEMICAL ENTITY: **PROPORTION**  $TWA (mg/m^3)$ STEL (mg/m<sup>3</sup>) CAS No. Alkaline powder various 60-80% not set not set Ingredients determined not to be hazardous Secret to 100% not set not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

#### 4. FIRST AID MEASURES

GENERAL INFORMATION: You should call the POISONS INFORMATION CENTRE if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 11 26 from

anywhere in Australia (0800 764 766 in New Zealand) and is available at all times.

Have this SDS with you when you call.

INHALATION: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove

> source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after

exposure.

SKIN CONTACT: Quickly and gently brush away excess solids. Wash gently and thoroughly with warm

water (use nonabrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or

discard. If irritation persists, repeat flushing and seek medical attention.

EYE CONTACT: Quickly and gently brush particles from eyes. Immediately flush the contaminated

> eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water

into the unaffected eye or onto the face. Obtain medical attention immediately.

**INGESTION:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons

Information Centre, or call a doctor.









SAFETY DATA SHEET

Page 4 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

### **5. FIRE FIGHTING MEASURES**

FIRE & EXPLOSION HAZARD: There is no risk of an explosion from this product under normal circumstances if it is

involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire.

Fire decomposition products from this product may be toxic if inhaled.

Take appropriate protective measures.

SUITABLE EXTINGUISHING MEDIA: Not Combustible. Use extinguishing media suited to burning materials.

FIRE FIGHTING: If a significant quantity of this product is involved in a fire, call the fire brigade.

FLASH POINT: Does not burn.

UPPER FLAMMABILITY LIMIT: Does not burn

LOWER FLAMMABILITY LIMIT: Does not burn

AUTOIGNITION TEMPERATURE: No applicable – does not burn.

FLAMMABILITY CLASS: Does not burn.

### 6. ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE:

In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. No special recommendations for clothing materials. Eye/face protective equipment should comprise as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that dusts are likely to build up in cleanup area, we recommend that you use a suitable Dust Mask. Use a P1 mask, designed for use against mechanically generated particles eg silica & asbestos. Stop leak if safe to do so, and contain spill. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Consider vacuuming if appropriate. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. Contaminated area may be neutralised by washing with weak or dilute acid. Vinegar, citrus juice and most soft drinks may be suitable. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

# SAFETY DATA SHEET

Page 5 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

### 7. HANDLING AND STORAGE

HANDLING: Keep exposure to this product to a minimum, and minimise the quantities kept in work

areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to

persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

STORAGE: This product is a Scheduled Poison. Observe all relevant regulations regarding sale,

transport and storage of this schedule of poison. Keep containers dry and away from water. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Check packaging - there may be further

storage instructions on the label.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: AS 1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZ S2210.

#### SWA Exposure Limits - TWA (mg/m3) / STEL (mg/m3)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

VENTILATION: No special ventilation requirements are normally necessary for this product. However

make sure that the work environment remains clean and that dusts are minimised.

EYE PROTECTION: Protective glasses or goggles should be worn when this product is being used. Failure

to protect your eyes may cause them harm. Emergency eye wash facilities are also

recommended in an area close to where this product is being used.

SKIN PROTECTION: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron.

Make sure that all skin areas are covered. See below for suitable material types.

PROTECTIVE MATERIAL TYPES: We suggest that protective clothing be made from the following material: PVC.

RESPIRATOR: If there is a significant chance that dusts are likely to build up in the area where this

product is being used, we recommend that you use a suitable Dust Mask. Eyebaths or eyewash stations and safety deluge showers should be provided near to where this

product is being used.









1 Tax: (02) 3004 1011 1 Email: Titlecolls@fil-tecolls.com.a.

# SAFETY DATA SHEET

Page 6 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

### 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DESCRIPTION & COLOUR: White deliquescent, alkaline powder

ODOUR: Odourless

ODOUR THRESHOLD: No data

BOILING POINT (°C): Not available

FREEZING/MELTING POINT (°C): Approximately 318°C

VOLATILES: No specific data. Expected to be below at 100°C

VAPOUR PRESSURE: Negligible at normal ambient temperatures

VAPOUR DENSITY: Not data

SPECIFIC GRAVITY: No data

WATER SOLUBILITY: No data

pH: No data. Will create alkaline solutions

VOLATILITY: Negligible at normal ambient tempratures

EVAPORATION RATE: No data

COEFF OIL/WATER DISTRIBUTION: No data

AUTO-IGNITION TEMPERATURE (°C): Not applicable – does not burn

#### 10. STABILITY AND REACTIVITY

REACTIVITY: This product is unlikely to react or decompose under normal storage conditions.

However, if you have any doubts, contact the supplier for advice on shelf life

properties.

INCOMPATIBLE MATERIALS: Water, acids.

CONDITIONS TO AVOID: Containers should be kept dry.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

# ETY DATA SH

Page 7 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

### 10. STABILITY AND REACTIVITY (CONT)

FIRE DECOMPOSITION: Only small quantities of decomposition products are expected from this products at

temperatures normally achieved in a fire. Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas. Oxides of sulfur (sulfur dioxide is a respiratory hazard) and other sulfur compounds.

Most will have a foul odour. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment,

and unconsciousness followed by coma and death.

POLYMERISATION: Polymerization will not occur.

#### 11. TOXICOLOGICAL INFORMATION

LOCAL EFFECTS (TARGET ORGANS): None known.

HAZARDOUS INGREDIENTS: No ingredient mentioned in the HSIS Database is present in this product at hazardous

concentrations.

INHALATION:

Significant inhalation exposure is considered to be unlikely. Available data indicates that this product is an inhalation irritant. Symptoms may include headache, irritation of (SHORT TERM EXPOSURE)

> nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has

ceased.

No data for health effects associated with long term inhalation. INHALATION:

(LONG TERM EXPOSURE)

SKIN CONTACT: Available data indicates that this product is a skin irritant. Symptoms may include (SHORT TERM EXPOSURE)

itchiness and reddening of contacted skin. Other symptoms may also become evident,

but all should disappear once exposure has ceased.

SKIN CONTACT: No data for health effects associated with long term skin exposure.

(LONG TERM EXPOSURE)

EYE CONTACT: Exposure via eyes is considered to be unlikely. This product is an eye irritant. (SHORT TERM EXPOSURE)

Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or

delayed treatment may cause permanent damage.

EYE CONTACT: No data for health effects associated with long term eye exposure.

(LONG TERM EXPOSURE)









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

# SAFETY DATA SHEET

Page 8 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

### 11. TOXICOLOGICAL INFORMATION (CONT)

INGESTION: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and

throat. Other symptoms may also become evident, but all should disappear once

exposure has ceased.

INGESTION: No data for health effects associated with long term ingestion.

(LONG TERM EXPOSURE)

CARCINOGEN STATUS: No significant ingredient is classified as carcinogenic by SWA.

No significant ingredient is classified as carcinogenic by NTP. No significant ingredient is classified as carcinogenic by IARC.

### 12. ECOLOGICAL INFORMATION

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

#### 13. DISPOSAL CONSIDERATIONS

DISPOSAL: This product may be recycled if unused, or if it has not been contaminated so as to

make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by some means. If neither of these options is suitable in-house,

contact a specialist waste disposal company.

### 14. TRANSPORT INFORMATION

**ROAD & RAIL TRANSPORT:** 

ADG REQUIREMENT Not classified as a Dangerous Good according to the Australian Code for the

Transport of Dangerous Goods by Road and Rail.

MARITIME TRANSPORT:

IMO/IMDG REQUIREMENT

Not classified as a Dangerous Good according to the criteria of the International

Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT:

ICAO/IATA REQUIREMENT

Not classified as a Dangerous Good according to the criteria of the International

Maritime Air Transport Association (IATA) Dangerous Goods Regulations for

transport by air.

#### 15. REGULATORY INFORMATION

AICS: All of the significant ingredients in this product are compliant with NICNAS regulations. The following ingredient: alkaline salts is mentioned in the SUSMP.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

# Y DATA SH

Page 9 of 9 Issue Date: 24 May 2017 Concrete Floor Powder

Version: 2

### 16. OTHER INFORMATION

CONTACT PERSON/POINT: General Manager 1300 796 009

> This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

> If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

LITERATURE REFERENCES:

- \* NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets.
- \* NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances.
- \* NOHSC: 10005 List of Designated Hazardous Substances.
- \* NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice.
- \* NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice.
- \* NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards.
- \* NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note.
- \* NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard.
- \* NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice.
- \* SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons
- \* ADG: Australian Dangerous Goods Code
- \* MSDS of component materials.

Supercedes document issued: 4<sup>th</sup> December 2012 LAST CHANGE:

Reason/s for revision: Minor editorial changes to comply with GHS requirements.

TN715042/1

**END OF SDS** 



