

SAFETY DATA SHEET

Page 1 of 8 Issue Date: 6 February 2017 Draw 49MMA Version: 2

Product Identifier:

Draw 49MMA

1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY:	Hi-Tec Oil Traders Pty Ltd. (ABN 28 053 837 362)
ADDRESS:	PO Box 322 Castle Hill NSW 1765 5 Tarlington Place, Smithfield NSW 2164
TELEPHONE NUMBER:	1300 796 009
FAX NUMBER:	(02) 9604 1611
EMERGENCY TELEPHONE NUMBER:	1300 796 009
PRODUCT NAME:	Draw 49MMA
OTHER NAMES:	None
MANUFACTURER'S PRODUCT CODE:	HI6- 2939
USE:	A heavy duty extendable drawing and stamping lubricant
ADDITIONAL INFORMATION:	Refer to Product Information Sheet for additional information
OTHER INFORMATION:	Visit our website: <u>www.hi-tecoils.com.au</u> Email: hitecoils@hi-tecoils.com.au

2. HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION:	NON-HAZARDOUS NON-DANGEROUS GOODS Hazard classification according to GHS Classification. Dangerous goods classification according to Australian Dangerous Goods Code.
SIGNAL WORD (S):	None
IRRITANCY OF PRODUCT:	Not classified as an irritant.
SENSITISATION OF PRODUCT:	Not known to be a sensitiser.
TERATOGENICITY:	No teratogenic effects known.
OTHER INFORMATION:	Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and environment on disposal. All used oils should be handled with caution and



AUSTRALIAN FAMILY OWNED SINCE 1989

skin contact avoided as far as possible.



SAFETY DATA SHEET

Page 2 of 8 Issue Date: 6 February 2017 Draw 49MMA Version: 2

3. IDENTIFICATION / COMPOSITION OF INGREDIENTS

CHEMICAL CHARACTERISTICS:	Liquid		
INGREDIENTS:-			
CHEMICAL ENTITY: Mineral Oil Ingredients determined not to be hazardous	CAS No. Proprietary Mixture	PROPORTION 60-90% To 100%	
OTHER INFORMATION:	The petroleum oil IP 346 test method	s in this product contain less than 3% DMSO extract as measured by l.	
4. FIRST AID MEASURES			
SWALLOWED:	Do not induce vor medical.	Do not induce vomiting. Give copious amounts of water to wash out mouth Seek medical.	
EYE:	be held apart. Tak	Immediately irrigate with copious amounts of water for at least 15 minutes. Eyelids to be held apart. Take care not to rinse contaminated water into non-affected eye. In all cases of eye contamination it is a sensible precaution to seek medical advice.	
SKIN:	water. If irritation skin requires URC debridement. Con	Remove contaminated clothing and wash skin thoroughly with plenty of soap and water. If irritation occurs, seek medical attention. High pressure injection through the skin requires URGENT medical attention for possible incision, irrigation and/or debridement. Contact with molten material will require treatment by a physician for burns (Do not remove material).	
INHALED:	to assume most co recovered. Seek m cyanotic (blue), er through face mask	om exposure to fresh air – avoid becoming a casualty. Allow patient omfortable position and keep warm. Keep at rest until fully nedical attention if effects persist. If breathing laboured and patient asure airways are clear and have qualified person give oxygen a. If breathing has stopped apply artificial respiration at once. In the rrest, apply external cardiac massage and seek urgent medical aid.	
FIRST AID FACILITIES:		n facilities are generally suitable. Ensure an eye wash station and vailable and ready for use.	
ADVICE TO DOCTOR:	Treat symptomatic	cally, for advice, contact the Poisons Information Centre 131 126	
OTHER INFORMATION:	Keep water and m	ild soap near work site.	





SAFETY DATA SHEET

Page 3 of 8 Issue Date: 6 February 2017 Draw 49MMA Version: 2

5. FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD

HAZARDS OF USE/STORAGE:	Combustible liquid, will readily burn under fire conditions.
HAZARDS FROM COMBUSTION PRODUCTS:	Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including oxides of carbon.
FIRE-FIGHTING RECOMMENDATIONS:	If safe to so, remove containers from path of fire. Keep storage tanks, pipelines, containers, fire exposed surfaces, etc. cool with water spray. Avoid spreading liquid and fire by water flooding.
PRECAUTION:	Water may cause splattering.
SUITABLE EXTINGUISHING MEDIA:	Use water, fog, foam, carbon dioxide or dry chemical.
PROTECTIVE MEASURES:	Fire fighters should wear self-contained breathing apparatus and full protective clothing if risk of exposure to vapours, fumes or products of combustion. Water spray may be used to cool down heat-exposed containers.
REACTIVITY:	May react with strong oxidising agents.

6. ACCIDENTAL RELEASE MEASURES

SPILLS & DISPOSAL:

Slippery when spilt. Avoid accidents, clean up immediately.

CLEAN-UP PROCEDURE - SMALL SPILLS (20L or less): Absorb or contain liquid with sand, earth or spill control material. Shovel up using non-sparking tools and place in a sound labelled sealable container for subsequent safe disposal. Place leaking containers in a sound labelled drum. Scrub contaminated surfaces with detergent solution. Retain washings as contaminated waste.

CLEAN-UP PROCEDURES - LARGE SPILLS (Greater than 20L): Transfer to a sound labelled, sealable container for product recovery or safe disposal. Treat residues as for small spills.

PERSONAL PRECAUTIONS: Extinguish naked flames. Remove ignition sources. No smoking. Avoid sparks. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Evacuate the area of non-essential personnel. Shut off leaks, if possible without personal risk. Do not breathe vapours. Ventilate contaminated area thoroughly. Dispose of according to local regulations.







SAFETY DATA SHEET

Page 4 of 8 Issue Date: 6 February 2017 Draw 49MMA Version: 2

6. ACCIDENTAL RELEASE MEASURES (CONT)

OTHER INFORMATION:

PROCEDURES IN CASES OF LEAKAGE OR BREAKAGE: Stop the source of the leak or release and contain spill if possible. Ventilate area. Use respirator and protective clothing outlined in this MSDS. Cover spill with inert absorbent earth. Use a stiff brush to mix thoroughly. Sweep up and place in a sound labelled disposable container. Scrub contaminated area with detergent and water using a stiff brush. Pick up liquid with additional absorbent material and place in a sound labelled disposable container. Prevent contamination of groundwater or surface water.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:	When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Prevent spillages. Ensure the appropriate personal protective equipment is used when handling this product. Ensure high level of personal hygiene is maintained when using this product. That is; always wash hands before eating, drinking smoking or using the toilet.
SAFE STORAGE CONDITIONS:	Keep containers closed at all times. Store in a cool place out of direct sunlight. Store away from oxidising agents. Check containers regularly for leaks.
CORROSIVENESS:	Not corrosive.
STORAGE REGULATIONS:	This is a Class C2 combustible liquid. Store in a well ventilated place away from ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Refer to AS 1940 – The Storage and Handling of Flammable Liquids, and NOHSC: 1015 – National Standard for Storage and Handling of Workplace Dangerous Goods for further information.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

NATIONAL EXPOSURE STANDARDS:	No exposure standard has been established for this product. NOHSC Exposure Standard: Oil mists – time weighted average (TWA) 5 mg/m ³ is recommended.
OTHER EXPOSURE INFORMATION:	Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL).
ENGINEERING CONTROLS:	Maintain concentration below recommended exposure limit. Special ventilation is not normally required. However, in the operation of certain equipment or at elevated temperatures mists or vapour may be generated and localised exhaust ventilation should be provided to maintain airborne concentration levels below the exposure



AUSTRALIAN FAMILY OWNED SINCE 1989

standard or the Manufacturer's recommended exposure standard.





SAFETY DATA SHEET

Page 5 of 8 Issue Date: 6 February 2017 Draw 49MMA Version: 2

8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT)

RESPIRATORY PROTECTION:	A respirator is not normally required. Airborne concentrations should be kept at lowest level possible. If vapours, mists or dusts are generated and the recommended exposure limit for the product is exceeded, use appropriate AS/NZS 1715/1716 approved half –face filter respirator suitable for organic vapours or air supplied respirator is worn. Air supplied respirators should always be worn when the airborne concentration of the contaminant or the oxygen content of the air is unknown
EYE PROTECTION:	Safety glasses, goggles or face shield as appropriate to AS/NZS 1337.
HAND PROTECTION:	Impervious or other suitable gloves conforming to AS/NZS 2161: Occupational Protective Gloves.
FOOTWEAR:	Industrial safety shoes.
BODY PROTECTION:	Suitable workwear should be worn to protect personal clothing, e.g. cotton overalls buttoned at neck and wrist or chemically resistant apron where clothing is likely to be contaminated. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial Clothing
HYGIENE MEASURES:	Always wash hands before eating, drinking, smoking or using the toilet. If contamination occurs, change clothing. Launder contaminated clothing before reuse. Discard internally contaminated gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM:	Liquid
APPEARANCE:	Clear brown liquid
COLOUR:	Brown
ODOUR:	Mild
MELTING POINT:	Not available
BOILING POINT, INITIAL, °C:	Not available
DENSITY @ 25°C (kg/L):	0.910 - 0.930
FLASHPOINT (OPEN CUP), °C:	>160
FLAMMABILITY LIMITS -LOWER:	Not available
FLAMMABILITY LIMITS -UPPER:	Not available







SAFETY DATA SHEET

Page 6 of 8 Issue Date: 6 February 2017 Draw 49MMA Version: 2

9. PHYSICAL AND CHEMICAL PROPERTIES (CONT)

FLAMMABILITY:	Combustible liquid.
AUTO IGNITION TEMPERATURE:	Not available
SOLUBILITY IN WATER:	Insoluble
VAPOUR PRESSURE:	Not available
VAPOUR DENSITY (AIR=1):	Not available
VISCOSITY @ 40 °C (cSt):	240 - 320
EXPLOSION PROPERTIES:	Not considered an explosion risk under normal conditions of use.
OTHER INFORMATION:	These physical data and other properties do not constitute a specification.

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable under normal conditions of use.
CONDITIONS TO AVOID:	Heat, direct sunlight, open flames or other sources of ignition.
INCOMPATIBLE MATERIALS:	Strong oxidising agents.
HAZARDOUS REACTIONS:	Will react with strong oxidising agents.
HAZARDOUS POLYMERISTION:	Will not occur.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY:	Not available
SKIN CORROSION / IRRITATION:	No information available.
SERIOUS EYE DAMAGE/ IRRITATION :	No information available.
SENSITISATION :	No information available.
REPRODUCTIVE TOXICITY:	No information available.
ASPIRATION HAZARD:	No information available.





SAFETY DATA SHEET

Page 7 of 8 Issue Date: 6 February 2017 Draw 49MMA Version: 2

11. TOXICOLOGICAL INFORMATION (CONT)

GERM CELL MUTAGENICITY:

No information available.

No information available.

No data available for this material.

No data available for this material.

No data available for this material.

CARCINOGENICITY:

No information available.

12. ECOLOGICAL INFORMATION

STOT (SINGLE / REPEATED EXPOSURE):

ECOTOXICITY:

PERSISTENCE / DEGRADABILITY:

MOBILITY:

ENVIRONMENT PROTECTION:

Do not allow material to enter drains, sewers or watercourses.

13. DISPOSAL CONSIDERATIONS

DISPOSAL CONSIDERATIONS:

Dispose of according to federal, E.P.A. and state regulations.

14. TRANSPORT INFORMATION

TRANSPORT INFORMATION:

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

15. REGULATORY INFORMATION

POISON SCHEDULE:Not classified as a Scheduled Poison according to the Standard for the Uniform
Scheduling of Drugs and Poisons SUSDP).PACKING & LABELLING:NilAUSTRALIAN INVENTORY STATUS:All components are listed.





SAFETY DATA SHEET

Page 8 of 8 Issue Date: 6 February 2017 Draw 49MMA Version: 2

16. OTHER INFORMATION

CONTACT PERSON/POINT:	General Manager 1300 796 009
	This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions. If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.
	Safety Data Sheets are updated frequently. Please ensure you have a current copy.
LITERATURE REFERENCES:	 * NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets. * NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances. * NOHSC: 10005 List of Designated Hazardous Substances. * NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice. * NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice. * NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards. * NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note. * NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard. * NOHSC: 2017 Storage and Handling of Drugs and Poisons * ADG: Australian Dangerous Goods Code * MSDS of component materials.
LAST CHANGE:	Supersedes document issued: 1 st March 2016. Reason/s for revision: Minor editorial changes to comply with GHS requirements.
TN712060/1	
END OF SDS	

