



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362
5 Tarlington Place Smithfield NSW 2164
Correspondence: P.O Box 322 Castle Hill NSW 1765
Ph: 1300 796 009 | **Fax:** (02) 9604 1611 | **Email:** hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

SAFETY DATA SHEET

Page 1 of 11
Issue Date: 28 March 2022
Hi Octane Boost & Clean
Version: 3

Product name: **Hi Octane Boost & Clean**

1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY: Hi-Tec Oil Traders Pty Ltd. (ABN 28 053 837 362)

ADDRESS: PO Box 322 Castle Hill NSW 1765
5 Tarlington Place, Smithfield NSW 2164

TELEPHONE NUMBER: 1300 796 009

FAX NUMBER: (02) 9604 1611

EMERGENCY TELEPHONE NUMBER: 1300 796 009

PRODUCT NAME: Hi Octane Boost & Clean

OTHER NAMES: None

MANUFACTURER'S PRODUCT CODE: HI8-3314

USE: Petrol fuel additive for boosting the octane rating, cleaning fuel injectors and combustion chamber

ADDITIONAL INFORMATION: Refer to Product Information Sheet for additional information

OTHER INFORMATION: Visit our website: www.hi-tecoils.com.au
Email: hitecoils@hi-tecoils.com.au

2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE: HAZARDOUS SUBSTANCE
NON-DANGEROUS GOODS
Hazard classification according to criteria of NOHSC and GHS .
Dangerous Goods classification according to Australian Dangerous Goods Code.

POISON SCHEDULE: None allocated



SIGNAL WORD: **DANGER**



AUSTRALIAN FAMILY OWNED SINCE 1989





SAFETY DATA SHEET

2. HAZARDS IDENTIFICATION (CONT)

GHS HAZARD CLASSIFICATION:

FLAMMABLE LIQUID:	Category 4
ACUTE TOXICITY (ORAL):	Category 3
ACUTE TOXICITY (DERMAL):	Category 4
ACUTE TOXICITY (INHALATION):	Category 2
CARCINOGENICITY:	Category 2
ASPIRATION HAZARD:	Category 1
SKIN CORROSION / IRRITATION:	Category 3
SPECIFIC TARGET ORGAN TOXICITY	
-SINGLE EXPOSURE:	Category 3 Narcotic effects
ACUTE AQUATIC HAZARD:	Category 3
CHRONIC HAZARD:	Category 3

HAZARD STATEMENTS:

H227: Combustible liquid.
H301: Toxic if swallowed.
H312: Harmful in contact with skin.
H330: Fatal if inhaled.
H351: Suspected of causing cancer.
H336: May cause drowsiness or dizziness.
H304: May be fatal if swallowed and enters airways.
H412: Harmful to aquatic life with long lasting effects.
EUH066: Repeated exposure may cause skin dryness and cracking.

PREVENTION STATEMENTS:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.
P210: Keep away from flames and hot surfaces. - No smoking.
P261: Avoid breathing vapor.
P264: Wash hands thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE STATEMENTS:

P304+P340+P312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call the POISON INFORMATION CENTER on 13 11 26 or physician if you feel unwell.
P301+P310+P330: IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth.
P331: Do NOT induce vomiting.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P362: Take off contaminated clothing and wash before reuse.
P332+P313: If skin irritation occurs: Get medical attention.

STORAGE STATEMENTS:

P405+P403+P235: Store locked up. Store in a well-ventilated place. Keep cool.

DISPOSAL STATEMENT:

P501: Dispose of contents and container in accordance with all local, regional, national and international regulations..





SAFETY DATA SHEET

Page 3 of 11
Issue Date: 28 March 2022
Hi Octane Boost & Clean
Version: 3

2. HAZARDS IDENTIFICATION (CONT)

OTHER HAZARDS: None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

DESCRIPTION: Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons with carbon numbers predominantly in the C9 to C16 range. May also contain several additives at <0.1% v/v each. May contain cetane improver (Ethyl Hexyl Nitrate) at <0.2% v/v.

CHEMICAL ENTITY	CAS NO	CONC.
Naptha petroleum, heavy aromatic hydrosulferised	64742-82-1	> 80%
Methyl cyclopentadienyl manganese tricarbonyl	12108-13-3	< 10%

4. FIRST AID MEASURES

GENERAL INFORMATION: You should call the Poisons Information Centre on 13 11 26 from anywhere in Australia (0800 764 766 in New Zealand) if you feel that you may have been poisoned, burned or irritated by this product. Have this SDS with you when you call.

INGESTION: Seek immediate medical attention. Do not induce vomiting.

EYE CONTACT: Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.

SKIN CONTACT: Wash contact areas with water. Remove contaminated clothing. Launder contaminated clothing before re-use.

INHALATION: Remove from further exposure. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with bag-valve-mask device or use mouth-to-mouth resuscitation.

FIRST AID FACILITIES: Eye wash fountains and safety showers should be available for emergency use.

ADVICE TO DOCTOR: Material if aspirated into the lungs may cause chemical pneumonitis. Treat appropriately.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water spray or fog, alcohol stable foam, dry chemical powder and carbon dioxide.





SAFETY DATA SHEET

5. FIRE FIGHTING MEASURES (CONT)

SPECIAL PROTECTIVE PRECAUTIONS AND EQUIPMENT FOR FIRE FIGHTERS:

Use water to cool fire-exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapours and to protect personnel attempting to stop leak. Water spray may be used to flush spills away from exposures. Prevent run off from fire control or dilution from entering waterways, sewers or drinking water supply. For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

UNUSUAL FIRE AND/ EXPLOSION HAZARDS:

Carbon monoxide may be evolved if incomplete combustion occurs. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Hazardous combustion products may include: oxides of sulphur.

6. ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURE:

Report spills as required to appropriate authorities such as local Environmental Health Officer or Fire Brigade. If spills are likely to enter any drain, waterway or groundwater, contact the Area Water Authority. In case of accident or road spill, contact police and fire brigade and if appropriate, the Area Water Authority.

SPILL/RELEASE PROCEDURE:

Eliminate all ignition sources. Contain and adsorb on suitable chemical absorbent material, etc. Shovel up and dispose of at an appropriate licensed waste disposal site in accordance with current applicable laws and regulations and product characteristics at time of disposal. Remove leaking containers to detached area.

ENVIRONMENTAL PROCEDURES:

Prevent spills from entering storm sewers or drains and contact with soil.

7. HANDLING AND STORAGE

GENERAL PRECAUTIONS:

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Air-dry contaminated clothing in a well-ventilated area before laundering. Prevent spillages. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Never siphon by mouth. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. Maintenance and Fuelling Activities - Avoid inhalation of vapours and contact with skin.

PRECAUTIONS FOR SAFE HANDLING:

Avoid breathing of or contact with material. Use only in well ventilated areas. Wash thoroughly after handling. Avoid inhaling vapour and/or mists. Avoid contact with skin, eyes, and clothing. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec). Avoid splash filling.



SAFETY DATA SHEET

Page 5 of 11

Issue Date: 28 March 2022

Hi Octane Boost & Clean

Version: 3

7. HANDLING AND STORAGE (CONT)

Do NOT use compressed air for filling, discharging, or handling operations. Vapours are heavier than air, beware of accumulation in pits and confined spaces. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Handling Temperature: Ambient.

Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge. Keep containers closed when not in use. Do not use compressed air for filling, discharging or handling.

CONDITIONS FOR SAFE STORAGE,
INCLUDING ANY INCOMPATIBILITIES:

Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Keep container tightly closed. Must be stored in a dyked (bundled), well-ventilated area, away from sunlight, ignition sources and any other sources of heat. Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a suitable vapour treatment system. Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

<u>Material</u>	<u>Source</u>	<u>Type</u>	<u>ppm</u>	<u>mg/m³</u>	<u>Notation</u>
Naphtha petroleum, heavy aromatic hydrosulferised	SG OEL	TWA	-	790	Can be absorbed through the skin
	ACGIH	TWA	No Limit	No Limit	
	ACGIH	SKIN_DES			
Methyl cyclopentadienyl manganetricarbonyl (12108-13-3)	ACGIH	TWA(mg/m ³)		0.2	
	NIOSH REL	TWA(mg/m ³)		0.2	

BIOLOGICAL EXPOSURE
INDEX (BEI):

No biological limit allocated.

ENGINEERING CONTROLS
VENTILATION:

Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:1997 : Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements





SAFETY DATA SHEET

Page 6 of 11

Issue Date: 28 March 2022

Hi Octane Boost & Clean

Version: 3

8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT)

APPROPRIATE ENGINEERING CONTROLS:

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Use sealed systems as far as possible. Firewater monitors and deluge systems are recommended. Eye washes and showers for emergency use.

PERSONAL PROTECTION

HAND PROTECTION:

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739, AS/NZS:2161) made from the following materials may provide suitable chemical protection: Longer term protection: Viton. Incidental contact/splash protection: Nitrile rubber. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

SKIN PROTECTION:

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

EYE PROTECTION:

Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

RESPIRATORY PROTECTION:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for organic gases and vapours [Type A boiling point > 65°C (149°F)] meeting EN 14387. Where respiratory protective equipment is required, use a full-face mask. Where air-filtering respirators are unsuitable (e.g., airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

BODY PROTECTION:

Chemical resistant gloves/gauntlets, boots, and apron. Where risk of splashing or in spillage clean up, use chemical resistant one-piece overall with integral hood. Wear antistatic and flame retardant clothing.

SMOKING & OTHER DUSTS:

Smoking must be prohibited in all areas where this product is used - see safety information on flammability.

THERMAL HAZARDS:

Not Applicable.





SAFETY DATA SHEET

Page 7 of 11
Issue Date: 28 March 2022
Hi Octane Boost & Clean
Version: 3

8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT)

GENERAL: Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapor.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM:	Clear dark amber to brownish liquid
ODOUR:	Hydrocarbon
ODOUR THRESHOLD:	Data not available
pH:	Data not available
BOILING POINT/RANGE (°C):	175 – 340
MELTING / FREEZING POINT (°C):	No data available
FLASH POINT - TAG CLOSED CUP (°C):	>65
FLAMMABILITY LIMITS (%):	No data available
EXPLOSION LIMITS (%):	No data available
AUTOIGNITION TEMPERATURE (°C):	No data available
VAPOUR PRESSURE:	No data available
RELATIVE DENSITY (g/cm ³):	0.810 – 0.820
WATER SOLUBILITY:	Negligible
SOLUBILITY IN OTHER SOLVENTS:	Data not available
n-OCTANOL / WATER PARTITION COEFFICIENT (log pow):	Data not available
DYNAMIC VISCOSITY:	Data not available
KINEMATIC VISCOSITY:	Data not available
VAPOUR DENSITY (AIR=1):	No data available
EVAPORATION RATE (nBu = 1):	Data not available





SAFETY DATA SHEET

Page 8 of 11
Issue Date: 28 March 2022
Hi Octane Boost & Clean
Version: 3

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable under normal conditions.
INCOMPATIBLE MATERIALS:	Strong oxidizers, Halogens, strong acids and alkalis. Do not allow molten material to contact water or liquids as this can cause violent eruptions, splatter hot material, or ignite flammable material.
CONDITIONS TO AVOID:	Heat, sparks, light, flame and build-up of static electricity.
HAZARDOUS DECOMPOSITION PRODUCTS:	Product does not decompose at ambient temperatures. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, manganese oxides, and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.
HAZARDOUS REACTIONS:	Will not occur.

11. TOXICOLOGICAL INFORMATION

BASIS FOR ASSESSMENT:	Information given is based on product data, knowledge of the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). Chronic hazard category 3.
ACUTE ORAL TOXICITY:	Oral: Toxic if swallowed. Dermal: Fatal in contact with skin. Inhalation: Fatal if inhaled. Inhalation:dust,mist: Not classified.
Methyl cyclopentadienyl manganese tricarbonyl (12108-13-3)	
ATE US (oral)	58 mg/kg body weight
ATE US (dermal)	140 mg/kg body weight
ATE US (gases)	100 ppmV/4h
ATE US (vapors)	0.500 mg/l/4h
ATE US (dust, mist)	0.050 mg/l/4h
LD50 oral rat	58 mg/kg
LD50 dermal rabbit	140 mg/kg
LC50 inhalation rat (mg/l)	76 mg/m ³ (Exposure time: 4 h)
LC50 inhalation rat (ppm)	0.247 ppm/1h
SKIN CORROSION/IRRITATION:	Irritating to skin.
RESPIRATORY OR SKIN/ SENSITISATION:	There is no data available.
RESPIRATORY IRRITATION:	Not expected to be a sensitiser.



SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION (CONT)

ASPIRATION HAZARD:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
MUTAGENICITY:	There is no data available.
CARCINOGENICITY:	Classified as a carcinogen.
REPRODUCTIVE AND DEVELOPMENTAL TOXICITY:	Not expected to impair fertility. Not expected to be a developmental toxicant.
SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE:	Category 3 Narcotic effects.
ADDITIONAL INFORMATION:	Classifications by other authorities under varying regulatory frameworks may exist.
AQUATIC HAZARD:	Harmful to aquatic life with long lasting effects.

12. ECOLOGICAL INFORMATION

TOXICITY:	There is no data available.
MOBILITY:	Spillages may penetrate the soil causing ground water contamination. This material may accumulate in sediments.
PERSISTENCE AND DEGRADABILITY:	There is no data available.
BIOACCUMULATIVE POTENTIAL:	There is no evidence to suggest bioaccumulation will occur.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:	Dispose of waste according to federal, EPA, state and local regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers.
-----------------	---

14. TRANSPORT INFORMATION

PROPER SHIPPING NAME:	Not regulated.
UN NUMBER:	Not regulated.
DG CLASS:	Combustible liquid.
SUBSIDIARY RISK 1:	None allocated.



SAFETY DATA SHEET

Page 10 of 11

Issue Date: 28 March 2022

Hi Octane Boost & Clean

Version: 3

14. TRANSPORT INFORMATION (CONT)

PACKAGING GROUP:	-
HAZCHEM CODE:	-
MARINE POLLUTANT:	Yes.
SPECIAL PRECAUTIONS FOR USER:	Refer to incompatibilities in section 7 and stability and reactivity information in section 10.
ADDITIONAL TRANSPORT REQUIREMENTS:	Nil.

15. REGULATORY INFORMATION

POISON SCHEDULE:	None allocated.
PACKING & LABELLING:	Refer to Section 14.
AUSTRALIAN INVENTORY STATUS:	All components are listed or exempted.

16. OTHER INFORMATION

CONTACT PERSON/POINT: General Manager 1300 796 009

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

LITERATURE REFERENCES:	<ul style="list-style-type: none">* NOHSC: 2011 National Code of Practice for the preparation of Safety Data Sheets.* Safe Work Australia: 2016 Preparation of Safety Data Sheets for Hazardous Chemicals.* NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances.* NOHSC: 10005 List of Designated Hazardous Substances.* NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice.* NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice.* NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards.* NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note.* NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard.* NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice.* SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons
------------------------	---





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362
5 Tarlington Place Smithfield NSW 2164
Correspondence: P.O Box 322 Castle Hill NSW 1765
Ph: 1300 796 009 | **Fax:** (02) 9604 1611 | **Email:** hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

SAFETY DATA SHEET

Page 11 of 11
Issue Date: 28 March 2022
Hi Octane Boost & Clean
Version: 3

16. OTHER INFORMATION (CONT)

- * ADG: Australian Dangerous Goods Code
- * SDS of component materials.

LAST CHANGE:

Supersedes document issued: 19 May 2017.

Reason/s for revision: Minor editorial adjustments to comply with GHS requirements.

MR223082/1

END OF SDS



AUSTRALIAN FAMILY OWNED SINCE 1989

